

A Cementitious, Resin Modified Base Coat for Hard Coat Stucco Systems.

STUCCO BASE

DESCRIPTION AND USE:

Multicoat's STUCCO BASE is a polymer modified cementitious base coat designed to be used vertically as a base coat for hard coat stucco systems and as a base coat for stucco being applied to insulated concrete forms (ICF). STUCCO BASE is designed to be used as a base coat under synthetic stucco finishes such as Multicoat's MULTI-TEX® STUCCO MIX.

ADVANTAGES:

- Single Component Packaging
- Just Add Water
- Low Cost
- Outstanding Bond Strength to Most Building Materials
- Easy to Apply / Does Not Have to be Primed
- Extremely High Flexural Strength
- Can be Sprayed or Pumped
- Environmentally Friendly, Cleans Up With Water



BASIC USE:

STUCCO BASE is a dry mix bagged material mixed with clean water on the jobsite to form a hard base coat for a variety of stucco applications ranging from traditional "scratch & brown", ICF Stucco or used as a base coat for applications to block, brick or other cementitious substrates in need of a "leveling" material.

COLOR:

STUCCO BASE will dry to a grey color.

PACKAGING:

STUCCO BASE is packaged in 65-lb bags.

COVERAGE:

STUCCO BASE will cover 70 - 80 sq. ft. when applied over 2.5 galvanized wire lath, 90 -100 sq. ft. when applied into fiberglass mesh for ICF, and 100 - 110 when applied to other masonry substrates such as block or poured in place walls.



SURFACE PREPARATION:

Substrate must be structurally sound, free from grease, oil, paint, dirt, dust, sealers, laitence, curing compounds, and any other foreign material which may prevent proper bonding. Cracks and imperfections must be repaired prior to application.

MIXING:

STUCCO BASE is field mixed with clean potable water to desired consistency based upon delivery method and finishing technique. Add 1-1/4 to 1-1/2 gallons of water per bag. Mix vigorously to disperse all lumps and to thoroughly wet all particles. Adjust to desired consistency by addition of dry material or small amount of water. Mix thoroughly for a maximum of 3 minutes. For best results allow material to set for 3 to 5 minutes, then add a small amount of water and re-break the material. Re-temper as needed.

APPLICATION:

For use as a base coat over metal lath or fiberglass mesh: Apply STUCCO BASE to the substrate thick enough to cover the outline of the mesh or lath. The outline of the mesh or lath can be visible but should not be felt. Thickness of the STUCCO BASE will vary due to thickness of the lath or fiberglass mesh being used.

For use as a leveling coat: Apply material to the area which needs to be leveled and finish by a variety of methods used in the trade.

LIMITATIONS:

Do not apply if precipitation is expected with twelve hours of application. Do not apply if ambient air temperature is 40° F and falling or 100° F and rising. Do not add other materials to the mixture of the product.

CLEANING:

Clean with warm soapy water immediately after use. Once dried, material will require mechanical means for removal.

STORAGE:

Store bags in a cool, dry location. Store away from direct contact with the ground or concrete. Protect from weather and other damage.

WARRANTY:

Materials are guaranteed with respect to uniformity and quality within manufacturer's specifications. Seller makes no other warranty, expressed or implied, regarding the use of its products. Since use of the product is beyond seller's control, the buyer assumes all risks of use. Seller's sole obligation shall be to replace the material if found to be defective. Seller shall not be liable for any damages, injury, loss, direct or consequential, resulting from use of its products.

Additional warranty available to certified applicators.



MULTICOAT® CORPORATION West Coast

Toll Free: (877) 685-8426
(949) 888-7100 Fax (949) 888-2555
Website: www.multicoat.com
E-mail: info@multicoat.com

MULTICOAT® PRODUCTS, INC. East Coast

Toll Free: (800) 660-6729
(304) 586-0616 Fax (304) 586-0620
Website: www.multicoat.com
E-mail: info@multicoat.com

Available Through: