

MATERIAL SAFETY DATA SHEET

Manufacturer's Name:

MULTICOAT CORPORATION
23061 ARROYO VISTA
RANCHO STA. MARGARITA, CA 92688

Date prepared or revised:
June 28, 2000

Information Telephone No
949-888-7100

SECTION I - PRODUCT IDENTIFICATION

Chemical name:
MULTI-TEX STUCCO MIX

SECTION II - HAZARDOUS INGREDIENTS

May contain the following:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>EXPOSURE LIMITS IN AIR (Give Units)</u>			
		<u>ACGIH TLV</u>	<u>OSHA</u>	<u>PEL</u>	<u>OTHER</u>
Ammonia	7664-41-7	25 ppm			50 ppm
Propylene Glycol	57-55-6	NE			
Preservative	4080-31-3	NE			
Coalescent	25265-77-4	NE			

SECTION III - PHYSICAL DATA

<u>Melting Point/Freezing Point:</u>	<u>Boiling Point:</u>	<u>Specific Gravity (Water = 1):</u>
0°C/32°F (Water)	100°C/212°F (Water)	1.6 to 1.8.
<u>Evaporation Rate (Butyl Acetate = 1):</u>	<u>Solubility in Water:</u>	<u>Vapor Pressure:</u>
Less than 1 (Water)	Dilutable Aqueous Dispersion	7mm Hg @ 20°C/68°F

Appearance and Odor:

White or colored plaster, mild ammoniacal or acrylic odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash point: Not Applicable

Auto Ignition Temperature: Not applicable

Extinguishing Media: Material is not combustible. Use Water.

Splatter:

The wet dispersion will splatter above 100°C/212°F (Boiling point of water).

Special Firefighting Procedures:

Firefighters should be equipped with self-contained breathing apparatus and full protective gear.

SECTION V - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:

Inhalation - Vapor or mist can cause headaches, nausea, and irritation of the nose, throat and lungs.

Skin Contact - May be irritating upon repeated or prolonged contact. Wash skin with soap and water after contact.

Eye Contact - Flush eyes with large amount of water for at least 15 minutes. Consult physician if irritation persists.

HAZARD RATING (NFPA 704)

HEALTH EFFECTS

The effects of over-exposure are based on acute toxicity profiles for a number of acrylic emulsions that are compositionally similar to the binder used in this product.

Typical values are:	Rate, oral LD50:	>5.0 g/kg
	Rabbit, dermal LD 50	>5.0 g/kg
	Rabbit	Eye irritation

Acute effects:	Non-toxic by ingestion. May cause eye and skin irritation
Chronic effect:	No known chronic health effects

FIRST AID/EMERGENCY PROCEDURES

Eye Contact:

Flush eyes immediately with running water for 15 minutes, including under eyelids. Consult a physician if irritation persists.

Skin Contact:

Wash with soap & water.

Inhalation:

Move subject to fresh air. If breathing is difficult consult a physician.

Ingestion:

Dilute with large amounts of water and consult physician.

SUSPECTED CANCER AGENT?

NO This product's ingredients are not found in the Federal OSHA, NTP, IARC

California employers using CAL-OSHA - regulated carcinogens must register with CAL-OSHA. CAL-OSHA and Federal OSHA carcinogen lists are similar.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None other than the above listed.

SECTION VI - REACTIVITY DATA

Stability: Stable.

Incompatibility: None

Hazardous Polymerization: Will not occur.

Conditions to Avoid: None known

SECTION VII - SPILL, LEAK AND DISPOSAL PROCEDURES

Spill response procedures (Include employee protection measures):

Normal clean up precautions of Section VII.

Preparing wastes for disposal (container types, neutralization, etc.):

May be salvaged for use or removed to a landfill dump in accordance with regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation and engineering controls:

Provide general ventilation and local exhaust ventilation to remove vapor or mist in confined spaces.

