

MATERIAL SAFETY DATA SHEET

Manufacture's Name:

Date prepared or revised:

March 1, 2013

Information Telephone No:
949-888-7100



MULTICOAT CORPORATION
23331 ANTONIO PARKWAY
RANCHO STA. MARGARITA, CA 92688

SECTION I – PRODUCT IDENTIFICATION

BG 2000

Waterbase Membrane

HMIS: H F R PP
0 0 0 G

SECTION II – HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>Cas Number</u>	<u>Content</u>	<u>Occupational Exposure Limits</u>
--------------------	-------------------	----------------	-------------------------------------

None by WHMIS/OSHA criteria

SECTION III – PHYSICAL DATA

<u>Boiling Range:</u>	<u>Evaporation Rate:</u>	<u>Vapor Density:</u>	<u>Volatile Organic Content:</u>
200-225 Deg. F	Slower than Ether	Heavier Than Air	2 grams/liter

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:

Flash Point: >300F

Lel: N/A

Extinguishing Media:

Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog.

Unusual Fire And Explosion Hazards:

Extinguishing media above is recommended on dried films of this material that is burning. This material is non-combustible, but dried films are capable of burning and supporting combustion when in contact with open flames.

Special Firefighting Procedures:

Observe recommended procedures in handling fire areas. Wear appropriate fire fighting equipment including a self contained breathing apparatus.

SECTION V – HEALTH HAZARD DATA

Effects of Overexposure:

Vapor odors may cause irritation in the upper and lower respiratory tracts, nausea, headache and dizziness. Eye Contact can cause irritation, redness, and tearing. Skin Contact can cause minor irritation. Ingestion can cause nausea, vomiting, diarrhea, and gastrointestinal irritation.

Medical Conditions Prone To Aggravation by Exposure:

Overexposure to vapors can produce headaches, dizziness and nausea.

Primary Route(s) of Entry: Inhalation, Ingestion.

Emergency and First Aid Procedures:

If affected by vapors, move person to fresh air. Apply artificial respiration to person who loses consciousness and call a doctor immediately. Treat eye and skin contact by thoroughly washing with clean water. If irritation persists see a doctor immediately. If material is ingested and the person is conscious give two glasses of water to drink and call a doctor immediately.

SECTION VI – REACTIVITY DATA

Stability: Stable

Hazardous Polymerization:

Will not occur.
Hazardous polymerization information is not established.

Conditions to Avoid:

Avoid temperatures below 40 degrees Fahrenheit. Avoid freezing conditions.

Incompatibility (Materials To Avoid):

Avoid materials that react with water, also strong acids and alkalais.

SECTION VII – SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released Or Spilled:

Dike and absorb spilled material with inert absorbent material such as sand, earth, and sawdust. Use rags to clean up small amounts of spilled material.

Waste Disposal Method:

Collect material contaminated absorbent and rags into a disposable container and dispose of in accordance to local, state, and federal regulations. Consult with your local hazardous waste regulations regarding landfill dumping.

SECTION VIII – SAFE HANDLING AND USE INFORMATION

Respiratory Protection:

Wear approved organic vapor respirator unless ventilation equipment is adequate to keep airborne concentrations below the exposure standards.

Ventilation:

General mechanical ventilation may be sufficient to keep product vapor concentrations below specified TLV ranges. If inadequate, use local exhaust.

Protective Gloves:

Use impermeable solvent resistant gloves to protect from skin contact.

Eye Protection:

Use safety goggles, chemical safety glasses and or face shields to protect eyes.

Other Protective Equipment:

Impermeable aprons and protective clothing are advised when working with this product. The use of head caps is recommended whenever possible.

Hygienic Practices:

Eye washes and safety showers in the workplace are recommended.

SECTION IX – SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling and Storing:

Keep containers closed when not in use. Do not store or handle near heat, flames and strong oxidants. Store in cool well ventilated area. Rotate stock by using older materials first. Inspect for leaks in all containers.

Other Precautions:

Do not store in freezing areas. Keep above 40 degrees Fahrenheit. Keep out of reach of children.

Disclaimer – The information contained herein is based on data considered accurate. However, no warranty, whether expressed or implied is made.